

## RGB+PLUS Line Mini-TrikLits RGB+Trik28-FCT



**Pitch:** 4-, 6-, 12-inch, custom **Bulb Count**: 5-, 10-, 25-light, custom

Wire Color: black, green, white Ends: thru-connect, terminated, eye-hole loop

Output	
LED Type	SMD5050
LED Channels	R-G-B
Greyscale	16-bit, 65,536 dimming levels
LED Quantity	2
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet), WEC+, MeshTek BLE
Max Lights before power injection	approx. 125L
Max Distance before Power Injection	approx. 100-feet
Electrical & Safety	
Input Voltage	12 VDC
Current	0.028 Amps
Power	0.336 Watts
Wire	22 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+5A-12V
Certifications	(c)UL listed, IP 66
Physical	
Diameter	28mm
Weight	approx. 0.04 lb.
Housing	polycarbonate
Bulb Style	faceted
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.





USA HQ Mechanicsburg, PA (717) 763-1055

www.minleonusa.com









