



RGB+PLUS Line TriKIts RGB+TriK42-FCT

In association with



Pitch: 4-, 6-, 12-inch, custom

Bulb Count: 5-, 10-, 25-light, custom

Wire Color: black, green, white, clear

Ends: thru-connect, terminated, eye-hole loop

Output	
LED Type	SMD5050
LED Channels	R-G-B
Greyscale	16-bit, 65,536 dimming levels
LED Quantity	2
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MeshTek BLE
Max Lights before power injection	approx. 200L
Max Distance before Power Injection	approx. 200-feet
Electrical & Safety	
Input Voltage	24 VDC
Current	0.015 Amps
Power	0.36 Watts
Wire	22 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+4A-24V
Certifications	(c)UL listed, IP 66, CE
Physical	
Diameter	42mm
Weight	approx. 1.2 oz. per bulb
Housing	polycarbonate
Bulb Style	faceted
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055
www.minleonusa.com



Specifications as of Jan. 2023 and are subject to change.

Powered by
MESHTEK