



RGB+Line Light Bar - Frosted/Narrow RGB+Bar-FN

In association with



Length: 1-meter

Style: frosted

Ends: thru-connect, terminated

Wire Color: black, white, green

Output	
LED Type	SMD 5050
LED Channels	R-G-B
LED Count	48 / meter
LED/Chip	6 / 1
Chip/Meter	8
Greyscale	16-bit, 65,536 dimming levels*
Viewing Angle	180-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Bars before power injection	18
Max Distance before Power Injection	approx. 60- feet / 18-meters
Electrical & Safety	
Input Voltage	24 VDC
Current	0.2 Amps / meter
Power	4.8 Watts / meter
Wire	18 AWG, 3C, UV protected
Inline power injection	via Minleon Power T's & 3A or 4A/24V
Physical	
Size	24mm wide / 47mm depth
Pitch	1-inch
Housing	polycarbonate
Connector Type	LLT twist-lock
Lead/End Wire length	6" (standard)
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com



Powered by
MESHTEK

* 8-bit via DDP.

Specifications as of May 2021 and are subject to change.