



RGB+Plus Line Mini-Color Tile RGB+MCT-12v

In association with



Output	
LED Type	COB10WRGB
LED Channels	R-G-B
LED Count	1
Greyscale	16-bit, 65,536 dimming levels*
Beam Angle	180-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lamps before power injection	10
Max Distance before Power Injection	100-feet
Electrical & Safety	
Input Voltage	12 VDC
Current	0.42 Amps / lamp
Power	5-watts
Wire	18 AWG, 3C, UV protected
Inline power injection	via Rainmin Power T+'s
Certifications	IP 65
Physical	
Housing	alluminum, powder coated base; glass cover
Size	4.65 x 5 x 1.6"
Weight (kg)	0.88 lbs.
Connector Type	LLT twist-lock
Mounting Option	ground stake, 180-degree adjustable
Lead/End Wire length	6" (standard)
Operating Temperature	Neg -25 to +55 Cel. / -13 to 130 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com



* 8-bit via DDP.

Specifications as of May 2021 and are subject to change.

Powered by
MESHTEK